



MARTIN LIMESTONE, INC.

A Division of New Enterprise Stone & Lime Co., Inc.

74 Kurtz Road • Denver, PA 17517
TEL 800.823.7866 • FAX 888.428.7501
www.martinlimestone.com

-Product Specifications-

PREMIUM DIAMOND-TEX®

ASTM D422*

Particle-Size Analysis of Soils

SIEVE SIZE	PERCENT PASSING
# 4	100.0%
# 8	96.7%
# 10	92.3%
# 16	83.0%
# 30	74.5%
# 50	68.4%
# 100	59.7%
# 200	46.6%

Sieve Analysis Soil Classification

<u>SOIL TYPE</u>	<u>CONTENT</u>
Sand:	51%
Silt:	33%
Clay:	16%

ASTM D698

Standard Proctor Analysis

Optimum Moisture Content: 11.0%	
<u>Maximum Dry Density (Loose)</u>	
LB/Cu. Ft.	124.70
TN/Cu. Yd.	1.68
<u>Maximum Wet Density (Compacted)</u>	
LB/Cu. Ft.	138.40
TN/Cu. Yd.	1.87

*Test results are an average of tests performed by the Diamond-Tex® quality control laboratory and an independent lab. Actual test results for a specific sample will vary slightly without affecting product performance.

Colen Layton
Quality Control Technician